

19VATC CLASS A CABLE**PHYSICAL DIMENSIONS**

COMPONENT		19VATC CLASS A
CONDUCTOR	Material	CCS/BC
	Dia. (mm)	1.02±0.01
DIELECTRIC	Material	Foam PE
	Dia. (mm)	4.65±0.10
SHIELD	Material	Al Foil + Al Braid+ Al Foil
	Coverage	40%-95%
JACKET	Material	PVC/PE
	Dia. (mm)	7.06±0.10

ELECTRICAL CHARACTERISTICS

IMPEDANCE(Ω)	75±3
VELOCITY OF PROPAGATION	83%
CAPACITANCE(PF/M)	53.1
STRUCTURAL RETURN LOSS(≥DB)	20

NOMINAL ATTENUATION [@ 68° F. (20° C)]

FREQUENCY(MHZ)	ATTENUATION (DB/100M)
5	1.8
50	4.6
100	7.1
200	9.0
400	13.0
800	19.0
862	19.8
950	20.9
1350	25.5
1750	29.60
2150	33.4
3000	40.6

We Can Offer Same As Per Customer's Requirement For Option! Mainly We Can Offer Wooden Drum, Plastic Drum, Pallet For Choice. Any Other Packing Requirement Can Be Acceptable.