

2RG6 + 2CAT5E**PHYSICAL DIMENSIONS**

COMPONENT		2*RG6	2*CAT5E
CONDUCTOR	Material	CCS/BC	BC
	Dia. (mm)	1.02±0.01	0.50±0.01
DIELECTRIC	Material	Foam PE	HDPE
	Dia. (mm)	4.57±0.10	0.90±0.03
SHIELDING	Material	(Al Foil + Al Braid)*2	No
	Coverage	95%	No
INNER JACKET	Material	PVC	PVC
	Dia. (mm)	7.54±0.10	5.0±0.10
OUTER JACKET	Material	PVC	
	Thickness(mm)	0.80±0.10	

ELECTRICAL CHARACTERISTICS

IMPEDANCE(Ω)	75±3	100±15
VELOCITY OF PROPAGATION	83%	69%
CAPACITANCE(PF/M)	53.1	5.6

NOMINAL ATTENUATION [@ 68° F. (20° C)]

RG6		CAT5E	
FREQUENCY(MHZ)	ATTENUATION (DB/100M)	FREQUENCY(MHZ)	ATTENUATION (DB/100M)
5	2.20	1.0	2.0
55	5.25	4.0	4.1
211	9.42	10.0	6.5
300	11.25	20.0	9.3
400	13.12	25.0	10.4
550	15.45	31.25	11.7
750	18.34	62.5	17.0
1000	21.46	100	20.1

We Can Offer Same As Per Customer's Requirement For Option! Mainly We Can Offer Wooden Drum, Plastic Drum, Pallet For Choice. Any Other Packing Requirement Can Be Acceptable.